

















General Survey Straumann

Product line	X-Line			K-Line		Z-Line
Insert RN						
Distance height	3.25 mm	4.75 mm	6.25 mm	1.50 mm	3.00 mm	3.75 mm
REF	I.01.02.X325	I.01.02.X475	I.01.02.X625	I.01.02.K150	I.01.02.K300	I.01.02.Z375
formaly Straumann No.	048.511*					

Denture magnet			
Distance height	2.65 mm	5.00 mm	3.15 mm
REF	U.00.01.X265R	U.00.01.K500	U.00.01.Z315
formaly Straumann No.	048.515*		

Positioning cuff/ Resilience ring						
Resilience	0.3 mm	0.3 mm	0.00 mm	0.00 mm	0.3 mm	0.3 mm
REF	P.00.01.X1	P.00.01.X2	P.00.01.K1	P.00.01.K2	P.00.05.K1	P.00.03.Z1
formaly Straumann No.	048.516*					

Impression post			
Distance height	6.95 mm	Please use the denture magnet for impression!	6.95 mm
REF	A.00.02.X695		A.00.02.Z695
formaly Straumann No.	048.014*		

Laboratory replica		 Stainless steel		
Distance height	9.00 mm	9.00 mm	7.50 mm	10.00 mm
REF	M.00.01.X900	M.00.05.X900	M.00.01.K750	M.00.01.Z1000
formaly Straumann No.	048.121*			

Torque wrench insert						
formaly Straumann No.	046.146*					
	In addition to the torque wrench insert for Straumann, we offer more torque wrench inserts for the most popular ratchets.					

* All product numbers marked with an asterisk *) refer to Straumann AG REF number system!