

















## General Survey XIVE/Frialit-2

Product line	X-Line	K-Line	Z-Line				
<b>Insert ø 3.40 mm</b>  Distance height REF	 3.00 mm I.06.05.X300	 4.50 mm I.06.05.X450	 2.00 mm I.06.05.K200	 3.50 mm I.06.05.K350			
<b>Insert ø 3.80 mm</b>  Distance height REF	 3.00 mm I.06.01.X300	 4.50 mm I.06.01.X450	 6.00 mm I.06.01.X600	 2.00 mm I.06.01.K200	 3.50 mm I.06.01.K350	 3.50 mm I.06.01.Z350	
<b>Insert ø 4.50 mm</b>  Distance height REF	 3.00 mm I.06.02.X300	 4.50 mm I.06.02.X450	 6.00 mm I.06.02.X600	 2.00 mm I.06.02.K200	 3.50 mm I.06.02.K350	 3.50 mm I.06.02.Z350	
<b>Insert ø 5.50 mm</b>  Distance height REF	 3.00 mm I.06.03.X300	 4.50 mm I.06.03.X450	 6.00 mm I.06.03.X600			 3.50 mm I.06.03.Z350	 5.00 mm I.06.03.Z500
<b>Insert ø 6.50 mm</b>  Distance height REF						 3.50 mm I.06.04.Z350	 5.00 mm I.06.04.Z500

<b>Denture magnet</b>  Distance height REF	 2.65 mm U.00.01.X265R	 5.00 mm U.00.01.K500	 3.15 mm U.00.01.Z315			
<b>Positioning cuff/ Resilience ring</b>  Resilience REF	 0.3 mm P.00.01.X1	 0.3 mm P.00.01.X2	 0.00 mm P.00.01.K1	 0.00 mm P.00.01.K2	 0.3 mm P.00.05.K1	 0.3 mm P.00.03.Z1
<b>Impression post</b>  Distance height REF	 6.95 mm A.00.02.X695	Please use the denture magnet for impression!	 6.95 mm A.00.02.Z695			
<b>Laboratory replica</b>  Distance height REF	 9.00 mm M.00.01.X900	 9.00 mm M.00.05.X900 Stainless steel	 7.50 mm M.00.01.K750	 10.00 mm M.00.01.Z1000		
<b>Torque wrench insert</b>						

In addition to the torque wrench insert for Frialit 2 screwdriver 45/5722, we provide a torque wrench insert for the most popular ratchets.